

DATA SHEET

> MAINTENANCE

Utiliser des produits nettoyants standards (détergents neutre)

DESCRIPTION

Plaque de protection en PVC

- Pour protéger le bas des portes des coups de pieds, le milieu des portes de la salissure des mains, les murs d'éventuels chocs de chariots, etc...
- Très bonne résistance à l'abrasion, aux rayures, aux salissures, aux produits chimiques, aux germes. En PVC teinté dans la masse exempt de métaux lourds. Ep. 2 mm
- surface légèrement grainée
- joints soudables. Bords droits. A encoller à la colle acrylique avec spatule A2.

Pour la protection des murs dans les couloirs
à coller sur une surface propre et dégraissée

USE

Se pose en recouvrement d'un revêtement mural ou du mur peint.

REFERENCE

Ref : 480002

MATERIAL

Profilé PVC d'une très grande résistance aux choc - Classement
résistance au feu Bs2 d0

Surface grainée

Conformité REACH

FITTING MODE

Vous assurer que le support soit propre et dégraissé. A encoller a la colle acrylique avec spatule A2. les joints sont soudable (utiliser outillage de soudure ROMUS)

The information contained in this document is provided for information purposes. Romus cannot be held liable for this information. The user or specifier will check the compatibility of the product technical data with the actual situation. Romus reserves the right to modify all or part of this document without prior notice.

Architect :

Project :

Email :

Tel :

Distributor :

Tel :

Email :